

TEFPASS® PVDF-HP PIPE

Suited for Ultra Purity Water System!

- ✦ Excellent chemical resist in common use to most of chemical products.
- ✦ No release any organic and inorganic substances.
- ✦ No add any stabilizer, pigment or additive.



- ✦ The surface will not propagate microorganisms. For the inside pipe, can be used by steam disinfecting.
- ✦ Simple installation and economical maintenance cost.
- ✦ To extrude and package up inside the clean room, ensure that the finished pipes keep clean and high quality.

Specification:

OD		PN 16	G.W. (Kg/M)	Length (mm)
Inch	mm	T(mm)		
1/2"	20	1.9	0.21	5000
3/4"	25	1.9	0.27	5000
1"	32	2.4	0.44	5000
1-1/4"	40	2.4	0.55	5000
1-1/2"	50	3.0	0.85	5000
2"	63	3.0	1.09	5000
2-1/2"	75	3.6	1.55	5000
3"	90	4.3	2.22	5000
4"	110	5.3	3.32	5000



4th Fl., No.12, Ming-Tsu E. Rd.,

Taipei, Taiwan, R.O.C.

Tel: +886-2-25976222(Rep.)

Fax: +886-2-25955626

<http://www.alliedsupreme.com>

Email: sales@alliedsupreme.com